

Star SAFIRE® II

MULTI-MISSION IMAGING SOLUTION;
AWR CERTIFIED FOR HH-60 AND UH-60
BLACKHAWK VARIANTS



APPLICATIONS

SEARCH & RESCUE
RECONNAISSANCE
BOARDER AND COASTAL PATROL
TARGET IDENTIFICATION
UAVS
FORCE PROTECTION



FEATURES

High-performance, long range imaging

Mil-qualified

Multiple payloads

5-Axis stabilization

Low-Light/Near IR CCD

Automatic target tracker

Industry leader

BENEFITS

The Star SAFIRE II's microscanned 320x240 mid-wave infrared array gives outstanding Detection, Recognition and Identification ranges in an affordable 15" imaging system.

Star SAFIRE II's hermetically sealed gimbal is battle-tested, AWR certified, and thrives in the harshest operating environments.

Star SAFIRE II's modular design and revolutionary optical bench allow simultaneous installation of up to 5 imagers in the same gimbal.

The SAFIRE-family of gimbals features 5-axis stabilization for solid imagery in rough conditions.

The CCD-TV camera has a low-light, near-IR mode that is useful in areas with minimal illumination.

Star SAFIRE II's dynamic target Autotracker follows maneuvering targets from moving aircraft, decreasing operator workload.

With over 1,200 SAFIRE systems installed on over 60 aircraft types around the world, the Star SAFIRE II is a solid performer in the definitive lineage of infrared imagers.



Star SAFIRE® II

THERMAL IMAGER

Sensor type	320x240 InSb focal plane array
Resolution	640x480
Wavelength	3-5µm response
FOVs	25° to 0.8°
Zoom ratio	29X

COLOR ZOOM CAMERA (OPTIONAL)

Sensor type	Color CCD-TV
Resolution	525 / 625 line (NTSC/PAL)
FOVs	28° to 2.7°
Zoom ratio	18X (+12X E-Zoom)

SPOTTER SCOPE (OPTIONAL)

Sensor type	Color CCD
Resolution	494 / 582 line (NTSC/PAL)
FOV	0.4°

LASER PAYLOADS (OPTIONAL)

Rangefinder	Max. range	20Km +/-5m
	Classification	Class 1 (Eyesafe)
Illuminator	Power	1W or 2W options
	Classification	Class 4
	Beam Divergence	1° x 1°
Pointer	Power	100mw
	Classification	Class 3b

SYSTEM PERFORMANCE

System type	5 axis stabilization
Az. coverage	360° continuous
El. coverage	+30° to -120°
Stability	<20 µ
Airspeed	405 KIAS

SYSTEM INTERFACES

Analog video	NTSC/PAL
Control	SCU/serial digital/MIL-STD-1553B/ARINC
Data	RS-232, RS-422, ARINC 419/429, MIL-STD-1553B

ENVIRONMENTAL

Standards	MIL-STD-810 & MIL-STD-461
Operating temperature	-40°C to 55°C

POWER REQUIREMENTS

Voltage	22-29 VDC (per MIL-STD-704E)
Consumption	200W (360W max)

DIMENSIONS, WEIGHT & MOUNTING

TFU Size	15" x 17.5" (380 mm x 450 mm)
TFU Weight	<96 lbs (<43 kg)
CEU Size	10.0" x 7.5" x 12.5" (254 mm x 191 mm x 318 mm)
CEU Weight	23.0 lbs (10.4 kg)
Mounting	compatible with UltraMedia and SAFIRE systems

OTHER OPTIONS & ACCESSORIES

Automatic Target Tracker, Navigation/Radar Interfaces, Quick-Disconnect Mounts, Displays & Recorders, Moving Map Systems

CORPORATE HEADQUARTERS

FLIR Systems, Inc.
27700A SW Parkway Ave.
Wilsonville, OR 97070
USA
PH: +1 800.727.3547

BOSTON

FLIR Systems Boston, Inc.
25 Esquire Road
North Billerica, MA 01862
USA
PH: +1 800.464.6372

SANTA BARBARA

FLIR Systems, Inc.
Indigo Operations
70 Castilian Dr.
Goleta, CA 93117
USA
PH: +1 888.747.3547

EUROPE

FLIR Systems Ltd.
2 Kings Hill Avenue
West Malling, Kent
ME19 4AQ
United Kingdom
PH: +44.1732.220011

CANADA

FLIR Systems Ltd.
5230 South Service Road
Suite 125
Burlington, ON L7L 5K2
Canada
PH: +1 800.613.0507

SWEDEN

FLIR Systems AB
Rinkebyvägen 19
P.O. Box 3
SE-182 11 Danderyd
Sweden
PH: +46.8.753.2500

MIDDLE EAST

FLIR Systems, Inc.
c/o Middle East Optronics
FZCO
Unit C-13
Dubai Airport Free Zone
P.O. Box 54262
Dubai
United Arab Emirates
PH: +9714.299.6898

www.flir.com

